

4 Channel H.264 DVR Kit with 4x CCD Cameras



DVR Specifications

Image Compression System	H.264 NTSC/PAL	HDD	1 SATA, supports up to 1TB
Video Input	4 channels 1.0Vp-p, 75ΩBNC	USB Interface	1PCS USB2.0 for backup and 1PCS USB1.1 for mouse
Video Output	2 channels 1.0Vp-p, 75Ω BNC	Motion Detection	Zone setup: PAL13 x 10 (130) NTSC13 x 8 (104)
Audio Input	4 channels 1.0Vp-p, 600Ω RCA	Serial Interface	RS-485
Audio Output	1 channel 1.0Vp-p, 600Ω RCA	Network Interface	RJ-45,10M/100M
Audio Compression	ADPCM	Power Source	DC 19V/3A
Recording Frame Rate	100 fps	Power Consumption	60W
Recording Resolution	PAL: 25/720 x 576; 50/720 x 288; 100/360 x 288 NTSC: 30/720 x 480; 60/720 x 240; 120/360 x 240	VGA Interface	Yes; Supports resolution: 1024 x 768, 800 x 600
Display Resolution	D1	Alarm In	4 CH
Video Playback	Supports 4 channels playback at the same time	Alarm Out	1 CH
		Operating Temperature	0~50°C
		Dimensions (WxLxH)	300mm x 250mm x 60mm

Camera Specifications

Image Sensor	1/4" Sony Super HAD CCD	Gain control	Auto
Effective Pixels	PAL:500(H) x 582(V) 510(H) x 492(V)	Shutter Speed	1/50 (1/60) - 1/100,000 (s)
Signal System	PAL/NTSC	White Balance	Auto
Sync System	Internal	S/N Ratio	More than 48db (AGC OFF)
Horizontal Resolution	420TV Line	Video Output	1.0Vp-p,75Ω (BNC)
Lens	3.6mm	Power Requirement	DC12V/140mA, 300mA (IR on)
Minimum Illumination	0Lux (IR on)	Operation temp.	-10°C ~ 50°C
Back Light Compensation	Auto	Weather proof	IP66